F 233





F 233		
Maximum Printing Speed	60,000 cph.	
Web width	Minimum 600 mm (23.6 inches) Maximum 915 mm (36 inches)	
Cut off Length	546, 578 mm (21½", 22¾") (Other cut-offs on request)	
Jaw cylinder ratio	2 - around cutting cylinder	
	3 - around pln/tucking cylinder3 - around jaw cylinder	
Type of folds	Half fold (Broadsheet)	
	Quarter fold Double Parallel Fold	

- Cylinder ratio 2:3:3
- Air cushioned 70° former
- AC Servo drive for RTF
- Folder drive option shaftless or mechanically connected
- 2 sets of nipping rollers with the option of variable drive for multiwebs
- Pneumatic clutch
- Driven Slitter
- Push button fold change over
- On the run adjustment of,
 - ½ fold bucket phasing
 - Lap
 - Chopper phasing of 1/4 fold
- Wide range of optional attachments like
 - Quarter Fold
 - 2 or 3 high formers
 - Cross perforation with on the run phasing
 - Stitcher
 - Wide range of shaftless draw roller modules



Sidhwa House, N.A. Sawant Marg, Colaba, Mumbai - 400 005, India. Phone: 91-22-2287 4815/4788/1191/0620. Fax: +91 22 2287 0702 Email: sales@manugraph.com Website: www.manugraph.com